



FICHA TECNICA

CALIDAD TAPIZ:

BASIC ARO


USO/NIVEL:

ENTRENAMIENTO - INICIACIÓN

CARACTERISTICAS TECNICAS:

1/10" velours uni	1/10" velours uni	1/10" Uni-Velours	1/10" cut-pile
100% polyamide	100% polyamide	100% Polyamide	100% nylon
RUG Vilt	DOSSIER Feütre	RÜCKEN Vlies	BACKING Feltback
POOLHOOGTE ± 3 mm	HAUTEUR DU VELOURS ± 3 mm	POLHÖHE ± 3 mm	PILE HEIGHT ± 3 mm
TOTALE HOOGTE ± 5 mm	HAUTEUR TOTALE ± 5 mm	GESAMTHÖHE ± 5 mm	TOTAL HEIGHT ± 5 mm
POOLGEWICHT ± 350 g/m ²	POIDS DU VELOURS ± 350 g/m ²	POLGEWICHT ± 350 g/m ²	PILE WEIGHT ± 350 g/m ²
TOTAAL GEWICHT ± 1.050 g/m ²	POIDS TOTAL ± 1.050 g/m ²	GESAMTGEWICHT ± 1.050 g/m ²	TOTAL WEIGHT ± 1.050 g/m ²
AANTAL NOPPEN/M ² ± 189 000	NOMBRE DE POINTS/M ² ± 189 000	NOPPEN/M ² ± 189 000	TUFT DENSITY/M ² ± 189 000
AANBEVOLEN LEGWIJZE • Verleggen op klettband • Universele fixeerlijm • Verhuislijm	POSE PRÉCONISÉE • Pose sur bandes auto-collantes • Produit de maintien • Fixateur	EMPFOHLENE VERLEGEART • Verlegen auf Klettband • Universalfixierung • Wiederaufnahmeklebstoff	INSTALLATION METHOD • Laid on hook tape • Release bond
GEBRUIK • Klasse 22+: Huishoudelijk • Comfort: 1 • Brandklasse m. E _f EN 13501-1 • Geschikt v. vloerverwarming	UTILISATION • Classe 22+: Domestique général • Confort: 1 • Classement feu E _f EN 13501-1 • Compatible avec sol chauffant • Résistance thermique: ISO 8302 0.12 m ² K/W	EINSATZ • Klasse 22+: stark • Komfort: 1 • Baustoffkl. E _f EN 13501-1 • Geeignet f. Fussbodenheizung • Wdw. ISO 8302: 0.12 m ² K/W	USAGE • Class 22+: General domestic • Comfort: 1 • Fire resist. E _f EN 13501-1 • Suitable f. floorheating
BIJZONDERHEIDEN • Soft@home	EXTRAS • Soft@home	EXTRAS • Soft@home	EXTRAS • Soft@home

HOMOLOGACIONES / CERTIFICACIONES / PICTOGRAMAS:



***** Datos protegidos por el Secreto Empresarial